

Technical Data Sheet

PRODUCT	COSMOS LAC Spray Metallic 334/335/336/338
DESCRIPTION/ USES	High gloss metallic paint with special effect pigments. It a quick drying product and can be used in metal, wood and ceramic surfaces. Ideal for the paint of objects for indoors and outdoors use, giving excellent adhesion and durable gloss.
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0.6-0.8 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
Solids w/w	10-15%
VOC content	610 g/L
Flash Point	-104 °C (based on propellant)
Drying time	Touch (20°C, Humidity<65%): 5-10min Through dry (20°C, Humidity <65%) : 1h Maximum hardness: 24 hours
Coverage	5m ² /L
Can Pressure	4bar (20 °C) , 8 bar (50 °C)
Contents	400ml
Application	Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. Best application temperature : 20 °C - 25 °C
After use	Spray holding the can inverted for 3''. Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.