



Technical datasheet

PUR PROTECT INTERIOR VARNISH



IDEAL FOR

- Can be applied to any types of wood, whether European or exotic.
- Recommended for decorating and protecting interior wood: furniture, ornaments, doors, etc.

PERFORMANCES

- Gives rich and intense colour to the wood and a sophisticated silky waxed / gloss finish.
- Provides excellent resistance to knocks, scratches, stains and water.
- Easy to use: does not run, perfect flow, fast drying and no unpleasant odours.

SURFACE PREPARATION

- VARNISHED WOOD: rub gently with fine grain sandpaper (240). If the varnish is chipped, strip with V33 SPECIAL WOOD STRIPPER. Rinse with water or V33 CLEANING SOLVENT. Let it for 24 hours.
- WAXED WOOD: take off the layers of wax with a wax remover. Rub gently with fine grain sandpaper (240) and remove dust.
- RESINOUS WOOD (teak, etc.): degrease using V33 CLEANING SOLVENT. Rub gently with fine grain sandpaper (240) and remove dust.

APPLICATION

Ideal conditions for application: on bare, clean, dry wood, between 12°C and 25°C during dry conditions, away from draughts and sunlight.

1- Stir well before and during use with a long wide stick to homogenise.

2 - Apply with a brush, mini-roller or spray gun following the grain of the wood and avoiding excessive build-up.

3 - Leave the first layer to dry for 3 hours.

4 - Sand gently with fine grain sandpaper (240) and remove the dust before applying the second coat. Let it dry.



PUR PROTECT products are designed in accordance with strict specifications **to be people, habitat and environmentally friendly whilst providing an excellent level of performance.**

They are subjected to standardised tests conducted by independent laboratories to demonstrate: the respect of indoor air quality as

defined by standard EN 16 000, emissions of VOC (Volatile Organic Components) lower than regulatory thresholds and the absence of hazardous substances (formaldehyde, etc.). For more information, see www.v33.fr

Packaging: 0.25L - 1L (6 shades) - 2.5L(Clear only)

Finishes: gloss - satin

Covering power in 1 coat for 2.5L: +/- 30 m²

Drying:

Touch dry: 30 min

Between 2 coats: 2 hrs

Complete: 24 hrs

Cleaning of tools: Water

Equipment: Varnish roller or flat brush

SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE

DO NOT ALLOW TO FREEZE

EUH208: Contains benzisothiazolinone. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). EU limit value for this product (cat. A/e): 130g/l (2010). This product contains max 6g/l VOC. Help to protect the environment - do not empty unused product into drains. Close the container after use.

NOVENTA S.A.

Πεθύμνου 1

106 82 Αθήνα

Tél : 210 – 8218502

Fax : 210 - 8218201

www.v33.com

G.S. Hadjiyiannis Logistics Ltd

PO Box 55004

3820 Limassol – Cyprus

+357-25-877430