

Technical Data Sheet

Rust-Oleum Chalky Finish Furniture Paint (Aerosol)
(Available in a range of 8 colours)

Renovate and transform furniture with Rust-Oleum Chalky Finish Furniture Paint. This paint can be used directly onto wood (bare or painted), brick, stone, plaster or any suitably primed rigid surface. Create a distressed look by rubbing back the paint finish.

Preparation: For best results, ensure surface is clean, dry and free from loose paint, mould & mildew, wax or oil. If wax has been used clean the surface thoroughly with a suitable wax remover. We recommend that bare wood should be sanded before painting. Hard glossy surfaces should be abraded before painting. Cover surrounding areas to protect from spray mist.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. To create a distressed look, apply two coats of contrasting colours. Allow to dry then lightly abrade with a damp scotchbrite pad or a stainless steel scourer. Abrade with the grain of the wood. Protect the distressed effect with Rust-Oleum Furniture Finishing Wax or Rust-Oleum Furniture Lacquer.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying & Recoating: Touch dry in 1 hour. Handle after 4 hours. Apply a second coat after 4 hours, if necessary. Full hardness after 16 hours.

Coverage: Up to 2m²/can. Coverage may vary depending upon spray technique, porosity or roughness of surface.

Limitations: Cap and/or label indicate approximate colour and finish. Not for use directly onto metal. Not a stain blocking product. Prime any surfaces where stain bleed may be an issue, including knots. If unsure, test on an inconspicuous area before painting. Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour/finish shown is for guidance only. Do not use on galvanised steel or surfaces that regularly exceed temperatures over 90°C. Apply only when temperature is between 10-32°C and relative humidity below 85%. Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. For further information please contact our Technical Services Department.

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.