



NEUTRAL WEATHER SEALANT

Superior interior/exterior mono-component, medium modulus silicone sealant for building joints and glazing applications. Dyna-Pro® Neutral silicone exhibits high resistance to UV radiation and harsh weather conditions. Sealant is highly flexible, slump resistant, easy to apply with superior adhesion to building material such as glass, concrete, most plastics, metals, painted wood etc. Short skinning and drying time.

Approvals



Features

- 100% silicone polymer
- Excellent UV and temperature extremes resistance
- Excellent unprimed adhesion to a variety of substrates
- Non-corrosive to metals
- Easy to apply and tool
- Low odor
- Color matching service – we match any color requested



WEATHER
RESISTANT



UV RESISTANT




100% SILICONE



QUICK TO DRY






PRIMERLESS
SUPERIOR ADHESION



COLOR ON DEMAND

Instructions

This sealant is ready to use. After suitable joint preparation and masking, the sealant is gunned into place and tooled within 5 minutes, using a spatula which has been dipped in soapy water. Remove masking tape immediately after tooling. If necessary, clean uncured material using an approved sealant remover. For removal of cured material, abrasion or other mechanical means may be needed.



Technical Data

Property	Unit	Value
Skin over time	Min	12
Extrusion rate 20°C 6.2Kg/cm2	g/min	223
Durometer Shore A, 3d/RT		>= 18
Tensile 3d/RT	MPa	>= 1.55
Elongation 3d/RT	%	>= 450

Surface Preparation

Surfaces must be clean, dry and free of grease, dust and frost. In case of renovation work, old sealant as well as old paint must be removed completely.

Priming

This product features adhesion to a variety of non-porous substrates; however, for specific substrates, priming may be necessary to improve adhesion. Please consult our Technical Service Department.

Shelf Life

16 months from date of production, when stored at or below 30°C in the original unopened container

Packaging

- 280 / 300 mL cartridge

Standard Colors



The information is offered in good faith and is believed to be accurate. It should not however be used in substitution for customer's tests to ensure that DYNA-PRO® products are safe, effective and compatible for the intended use. Sole warranty is that the product will meet the DYNA-PRO® sales specifications in effect at the time of delivery. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.