

AREXOL

Bitumimous Primer



DESCRIPTION

AREXOL is a high-standard one-component, bituminous, solvent-based solution. In its final form, it creates a black, glossy watertight film, with excellent adhesion and high penetration on surfaces.

PRIMARY USES

AREXOL is used mainly as a primer for bonding bituminous waterproofing membranes, for the anticorrosion protection and waterproofing of metal surfaces and for the protection of concrete constructions,

It is not compatible with polystyrene, due to the existence of solvents.

COMPOSITION

Bitumen and selected organic solvents.

PACKAGING

AREXOL is available in metallic pails of 1, 5, and 18 L.

Drum of 180 L is available upon request.

TYPICAL PROPERTIES

Color	Black
Odor	Characteristic
Solid Content (ASTM D 41)	60 – 70% w/w
Solvent Content (ASTM D 41)	>30% w/w
Viscosity 25 °C (Brookfield) (ASTM D 2196)	2900 – 3200 cp (sp 3, rpm20)
Density (ISO 2811)	0.94±0.05 g/cm ³
Adhesion to Concrete (ASTM D 4541)	> 30 kg/cm ²
Absorption (H ₂ O - 10 days)	< 0,7 %

APPLICATION

The surface must be clean, free of oils, grease, moisture, and any residues, before use.

It can be applied with a bristle brush, paint roller, or airless spray. For even better results, it can be applied in two layers. Allow each coat to fully dry and then apply in a crossed-over manner. For bonding bituminous membranes, one coat is adequate which needs to be fully dried before applying blowtorch (usually 3 h for the solvents to evaporate - Full resistance will be achieved after 48 hours). If necessary, **AREXOL** can be diluted with a small quantity of Xylol.

ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th Km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 566

N.ARTAKI EVIA
RoofTile Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

AREXOL

Bitumimous Primer



If the material is to remain exposed to sunlight for a long period, it is recommended to be protected with bituminous aluminum paint **RECTIFLEX**. Do not apply **AREXOL** in direct sunlight exposure and during rainfall. Protect the fresh applied material from immediate rainfall during curing.

CONSUMPTION

The consumption depends on the amount of absorption and the structure of the surface.

Indicative per layew for:

- concrete surfaces 0,300 – 0,400 L/m²
- metal surfaces, 0,100 – 0,200 L/ m².

STORAGE

Use the product within one (1) year from the date of production. It should be stored indoors

and at temperatures from 5-35°C. Close the package tightly after each use.

Storage under not recommended conditions will result in deterioration of the product or packaging.

SAFETY

The material is classified as dangerous according to European Regulation 1272/2008. Keep away from sparks and flames. Do not smoke. Do not inhale, avoid contact with eyes and mouth, and in case you apply it by airless spray use a mask.

Do not apply in closed spaces without adequate air supply. In liquid form the material contaminates the water. Do not pour it on the ground or water. Always follow the related rules. For additional information refer to the SDS of this material.

The information contained in this publication of RAVAGO HELLAS SA is believed to be accurate and provided in good faith, based on our current knowledge and experience, when the products are stored, used, and applied under the prescribed conditions. Nevertheless, is up to the Users to satisfy the suitability of the product for their own specific purpose.



ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th Km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 566

N.ARTAKI EVIA
Rooftile Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214