

THE COMPLETE WOODSTAIN THAT PROTECTS YOUR EXTERIOR WOODS

EFFECTIVE PROTECTION

- Water repellent microporous formulation: lets the wood breathe by blocking water and moisture.
- Easy application.

AN EASY PRODUCT

- Compatible with all types of wood and on all woodstains previously applied
- Easy to renew, without sanding or stripping.

COLOURCHART

11 shades - SATIN



CLEAR



GOLDEN PINE



LIGHT OAK



GOLDEN OAK



MEDIUM OAK



TUDOR OAK



DOUGLAS



WALNUT



CHESTNUT



EBONY



ROSEWOOD



0,75L · 2,5L



SURFACES

For all exterior vertical
woodwork: shutters,
gates, fences, windows,
beams, cladding, garden
houses...

On all types of new and old
European and exotic woods.



DRYING TIME

3 h BETWEEN COATS

24 h COMPLETE



COVERAGE / L

+/- 6m²

FINISHED IN 2 COATS



TOOLS

BRUSH, ROLLER, SPRAY GUN



TOOL CLEANING

WHITE SPIRIT

DIRECTIONS FOR USE

PREPARATION

The wood to be stained must be clean, dry, healthy and not greasy. Sand the corners and edges to round them slightly.

• **RAW WOOD:** sand with sandpaper to obtain a smooth surface and remove dust. Pre-treat your wood with the V33 Multi use Wood treatment.

• **EXOTIC, BLACK WOODS, OAK:** apply first a suitable undercoat.

• **GREASY WOODS:** degrease.

• **ALREADY STAINED WOODS:** brush to remove non-adhering parts. Sand with sandpaper to obtain a smooth surface and remove dust.

APPLICATION

Ideal application conditions: between 12 and 25°C in dry weather and without draft.

Milky appearance in the tin will disappear after drying.

• Stir well the stain before and during use with a long and large stick.

• Apply with 2 coats with a brush, a roller or a spray gun (10% dilution).

• Between coats: proceed to a slight sanding with fine abrasive paper to obtain a smooth surface and remove dust.

• Remove as much woodstain as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

GOOD TO KNOW

Be careful: the colour in the tin does not correspond with the final colour/-shade.

On new or heavy exposed woods, it is recommended to apply a third coat as far as the lighter colours/shades are concerned.

6 YEARS GUARANTEE

The 6-year duration concerns:

- new or to renovate woods from common species: in accordance with the method of preparation and application.
- on vertical woodwork only.

South and South-West exposure: apply 3 layers.

The guarantee is limited to reimbursement of the product (on presentation of the bottle and the receipt) and covers only the appearance of the woodstain.

The 6 years duration depends on the exposure and on the weather conditions.

This period may be reduced in the event of severe weather conditions or of surfaces in constant exposure with moisture when the water can not run.