

THE MUST HAVE FOR YOUR DECKING !

Want to enjoy your wooden decking ? V33 Classic Decking Oil is ideal for feeding and protecting your decking from water, UV rays, stains and grease.

EFFICIENT

- Deeply impregnates the wood and protects it from water, stains and grease thanks to its waterproofing power.
- Microporous : allows the wood to breathe while protecting it from UV rays..

EASY

- Easy to apply and maintain.
- Compatible with any kind of wood.

COLOURCHART


2 shades - MAT



CLEAR



TEAK



2,5L · 5L


SURFACES

- Recommended for horizontal wood: deck flooring, wooden slabs, duckboards, etc.
- On all woods: European or autoclaved, teak or exotic, untreated or already oiled.



DRYING TIME

15 min BETWEEN COATS
24 h COMPLETE



COVERAGE / L

+/- 4m²
FINISHED IN 2 COATS



TOOLS

BRUSH, ROLLER (3-5mm short hair)



TOOL CLEANING

WHITE SPIRIT

DIRECTIONS FOR USE

PREPARATION

Ensure the surface is clean, dry and free from previous finishes and dust.

- **RAW WOOD** : lightly sand and remove dust.
- **OLD WOOD** : Clean with the V33 Decking cleaner.

APPLICATION

Apply the product in temperatures between 12°C and 30°C in dry weather.

Stir the Classic Decking Oil vigorously with a long, wide stick to ensure it is well blended before use.

- **1st application**: Saturate the wood generously, applying the oil with a brush or roller. Let it soak in for 15 minutes (varies depending on the wood type), then apply a second coat without waiting for the first to dry (wet on wet). Wipe off excess oil with a lint-free cloth. Repeat this process if there are any dull areas on the wood. Let it dry for 24 to 48 hours.

- **Maintenance**: Apply 1 to 2 coats of oil to dull areas. The seams are invisible.

Remove as much of the oil as possible from the tools after use. Do not dispose of residues and washing water/-solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

GOOD TO KNOW

- To ensure the wood is sufficiently oiled, run a few drops of water over it. If they bead on the surface, the wood is waterproofed. If not, or if the wood darkens upon contact with water, apply a new coat of oil.
- The color, porosity, species, and age of the wood can influence the final shade of the treated surface. The 'Natural' variant (colorless, non-pigmented) can naturally restore the original warm hue of discolored wood. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.
- For localized stains, clean with V33 Decking Cleaner.